





**SAFETY DATA SHEET
VAPOR BARRIER**

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: VAPOR BARRIER PART A	Product Use: MOISTURE MITIGATION COMPONENT
Manufacturer's Name: Concure Systems	Emergency Telephone: 480-820-7171
Address: Phx, AZ	Telephone Number: 480-820-7171
Date Prepared: DECEMBER 2014	Date Updated: March 1, 2017

SECTION 2: HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION	
	
	GHS07
Skin Irritant 2	H315 Causes skin irritation.
Eye Irritant 2	H318 Causes serious eye damage.
Skin Sensitization 1	H317 May cause an allergic skin reaction

LABEL ELEMENTS	
Hazard Pictogram:	
	
Signal Word: Danger	
Hazard Statements: Irritant.	
H315 – Causes skin irritation.	
H317 – May cause an allergic skin reaction.	
H318 – Causes serious eye damage.	
H332 – Harmful if inhaled.	
H335 – May cause respiratory irritation.	
Precautionary Statements:	
P101 – If medical advice is needed, have product container or label at hand.	
P102 – Keep out of reach of children.	
P202 – Do not handle until all safety precautions have been read and understood.	
P233 – Keep container tightly closed.	
P234 – Keep only in original container.	
P260 – Do not breathe dust/fume/gas/mist/vapors/spray.	
P262 – Do not get in eyes, on skin, or on clothing.	
P264 – Wash thoroughly with plenty of water immediately after handling.	
P270 – Do not eat, drink or smoke when using this product.	

CONCURE VAPOR BARRIER PART A SAFETY DATA SHEET

P271 – Use only outdoors or in a well-ventilated area.
P273 – Avoid release to the environment and drains.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.
P284 – Wear respiratory protection.
P314 – Get medical advice/attention if you feel unwell.
P391 – Collect spillage.
P402 + P404 – Store in a dry place. Store in a closed container.
P403 + P233 – Store in a well-ventilated place. Keep container tightly closed.
P405 – Store locked up.
P501 – Dispose of contents and container as hazardous waste in accordance with all local, regional, national and international regulations.

ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.
2.0 % of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

MATERIAL OR INGREDIENT	CAS #	WT. %
Aqua Ammonia	1336-21-6	< 0.1 %
Exact composition percentage/concentration has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.		

SECTION 4: FIRST-AID MEASURES

DESCRIPTION OF THE FIRST AID MEASURE

P301 + P310 + P330 + P331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.
P302 + P352 + P361 – IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get immediate medical advice/attention.
P304 + P311 + P340 + P341 + P342 – IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P305 + P313 + P337 + P338 + P351 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
P306 + P360 – IF ON CLOTHING: Immediately rinse contaminated clothing and skin with plenty of water before removing clothes.
P314 – Get medical advice/attention if you feel unwell.

IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: May cause moderate eye irritation.

Skin: Brief contact may cause moderate skin irritation with local redness. Prolonged skin contact is unlikely to result in absorption of harmful amounts. Has caused allergic skin reactions in humans.

Inhalation: At room temperature, exposure to vapor is minimal due to low volatility. Vapor from heated material, mist or aerosols may cause respiratory irritation.

Ingestion: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Chronic Health Hazard: This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately. Corticosteroid cream has been effective in treating skin irritation.

Specific Treatments: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. In case of accident or if you feel unwell, seek medical advice immediately (provide label or SDS).

SECTION 5 – FIRE-FIGHTING MEASURES

FLAMMABILITY

Flammability: Not flammable by WHMIS/OSHA criteria.

EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use extinguishing media appropriate for the surrounding fire. Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: During a fire, smoke may contain combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Styrene monomers. Acrylic monomers. Carbon monoxide. Carbon dioxide. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Contain fire water run-off if possible. Firewater run-off may cause environmental damage.

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use self-contained breathing apparatus and chemically protective clothing. Wear suitable protective clothing, gloves and eye/face protection. Open enclosed spaces to outside atmosphere. Evacuate personnel to safe areas and do not approach spilled product. If possible, stop flow of product.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN - UP

Methods for Containment: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. High pH of this material is harmful to aquatic life.

Methods for Cleaning-Up: Contain spilled material if possible. Absorb with materials such as: Sand. Vermiculite. Clay. Natural fiber products. Synthetic fiber products. Remove residual with soap and hot water. Collect in suitable and properly labeled containers. Provide adequate ventilation.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling: Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Do not swallow. Do not breathe vapor or mist. Wash thoroughly after handling.

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in air-tight labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Store in a temperature controlled area between 10°C (50°F) and 30°C (90°F).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS		
Exposure Guidelines		
Ingredient	Occupational Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Aqua Ammonia	35 mg/m ³ TWA 27 mg/m ³ STEL	25 ppm TWA 35 ppm STEL

EXPOSURE CONTROLS

Engineering Controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Wear approved face (face shield) protection or properly fitted splash-proof chemical safety goggles.

Skin Protection:

Hand Protection: Wear suitable impervious Neoprene gloves, PVC disposable gloves, or Nitrile rubber gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved Mist Respirator or filtering facepiece. Respirators should be selected by and used under the direction of a trained health and safety professional following OSHA and ANSI requirement standards.

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Color	Milky White / Off-White
Odor	Mild Ammonia Odor
pH	10 to 12
Melting Point/Freezing Point	1°C (34°F)
Initial Boiling Point and Boiling Range	100°C (212°F)
Flash Point	> 122 °C (Setaflash Closed Cup)
Evaporation Rate	Not Available
Flammability	Non Flammable
Lower Flammability/Explosive Limit	Not Available
Upper Flammability/Explosive Limit	Not Available
Vapor Pressure	Not Available
Vapor Density	Not Available
Relative Density/Specific Gravity	1.0 to 1.1
Solubility	Partial
Partition coefficient: n-octanol/water	Not Available
Auto-Ignition Temperature	Not Available
Decomposition Temperature	Not Available
Oxidizing Properties	No
Explosive Properties	No

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY
Stable under normal conditions and conditions of normal use.
CHEMICAL STABILITY
Stable under normal storage conditions and conditions of normal use.
POSSIBILITY OF HAZARDOUS REACTIONS
No dangerous reaction known under conditions of normal use. Hazardous polymerization will not occur.
CONDITIONS TO AVOID
Avoid temperatures above 177°C (350°F). Toxic decomposition products may be formed.
INCOMPATIBLE MATERIALS
Strong oxidizers. Strong mineral acids.
HAZARDOUS DECOMPOSITION PRODUCTS
May include, and are not limited to: acrylic monomers, oxides of carbon and nitrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS						
Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.						
Symptoms related to physical/chemical/toxicological characteristics:						
Eye: May cause serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.						
Skin: Symptoms may include redness, edema, drying, defatting and cracking of the skin. Do not allow continuous, prolonged contact with skin. May cause sensitization by skin contact.						
Inhalation: May cause respiratory tract irritation.						
Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.						
Acute Toxicity:						
<table border="1"> <thead> <tr> <th>Ingredient</th> <th>LC50</th> <th>LD50</th> </tr> </thead> <tbody> <tr> <td>Aqua Ammonia</td> <td>1 hr. Aerosol 9.85 mg/L, rat</td> <td>Oral 350 mg/kg, rat</td> </tr> </tbody> </table>	Ingredient	LC50	LD50	Aqua Ammonia	1 hr. Aerosol 9.85 mg/L, rat	Oral 350 mg/kg, rat
Ingredient	LC50	LD50				
Aqua Ammonia	1 hr. Aerosol 9.85 mg/L, rat	Oral 350 mg/kg, rat				
Calculated overall Chemical Acute Toxicity Values						
<table border="1"> <thead> <tr> <th>LC50 (inhalation)</th> <th>LD50 (oral)</th> <th>LD50 (dermal)</th> </tr> </thead> <tbody> <tr> <td>Not available.</td> <td>Not available.</td> <td>Not available.</td> </tr> </tbody> </table>	LC50 (inhalation)	LD50 (oral)	LD50 (dermal)	Not available.	Not available.	Not available.
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)				
Not available.	Not available.	Not available.				
<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*</th> </tr> </thead> <tbody> <tr> <td>Aqua Ammonia</td> <td>Not listed.</td> </tr> </tbody> </table>	Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*	Aqua Ammonia	Not listed.		
Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*					
Aqua Ammonia	Not listed.					
(* See Section 15)						
DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT-TERM AND LONG-TERM EXPOSURE						
Skin Corrosion/Irritation: May cause skin irritation.						
Serious Eye Damage/Irritation: May cause serious eye damage.						
Respiratory Sensitization: Based on available data, the classification criteria are not met.						
Skin Sensitization: May cause an allergic skin reaction.						
STOT-Single Exposure: May cause respiratory irritation.						
Chronic Health Effects:						
Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.						
Germ Cell Mutagenicity: Not hazardous by WHMIS/OSHA criteria.						

CONCURE VAPOR BARRIER PART A SAFETY DATA SHEET

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Not available.

Aspiration Hazard: Based on available data, the classification criteria are not met.

Toxicologically Synergistic Materials: Not available.

Other Information: Not available.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

Toxicity to fish - Components

Aqua Ammonia LC50 (96 h): 0.89 mg/l.

Toxicity to aquatic invertebrates - Components

Aqua Ammonia LC50 (48 h): 101 mg/l.

PERSISTENCE AND DEGRADABILITY

Not available.

BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

MOBILITY IN SOIL

Not available.

OTHER ADVERSE EFFECTS

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other Disposal Recommendations: Not available

SECTION 14: TRANSPORT INFORMATION

UN NUMBER

Not regulated.

UN PROPER SHIPPING NAME

Not applicable.

TRANSPORT HAZARD CLASS (ES)

Not applicable.

ENVIRONMENTAL HAZARDS

Not available.

SPECIAL PRECAUTIONS

Do not handle until all safety precautions have been read and understood.

SECTION 15: REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

CONCURE VAPOR BARRIER PART A SAFETY DATA SHEET

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Aqua Ammonia	None.	None.	1000	1336-21-6

California Proposition 65: This product does not contain chemicals known to the state of California to cause cancer.


WHMIS Classification(s):

- Class D2A - Chronic Toxic Effects
- Class D2B - Skin/Eye Irritant

TSCA:

Ingredient	USA TSCA LISTED
Aqua Ammonia	Yes.

WHMIS Hazard Symbols:



NFPA National Fire Protection Association	
Health:	2
Fire:	0
Reactivity:	0

HMS-Hazardous Materials Identification System	
Health:	2*
Fire:	0
Reactivity:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

*** SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:**

CP65

California Proposition 65

OSHA (O)

Occupational Safety and Health Administration.

ACGIH (G)

American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

IARC (I)

International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N)

National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

SECTION 16: OTHER INFORMATION

Date of Preparation:	December 22, 2014
Version:	1701
Revision Date:	January 2, 2017
Prepared by:	

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Material Safety Datasheet (MSDS)

VAPOR BARRIER PLUS

Manufacturer's Name: Concure Systems

Manufacturer's Address: 710 Trainer St. Chester, PA 19013

Phone Number: (480) 820-7171

Fax Number: (480) 820-7787



Section II – Hazardous Ingredients / Identity Information

Hazardous Components (Specify Chemical Identity: Common Name(s)) OSHA PEL ACGIH TVL other limits recommended % (optional)

<u>CAS Number</u>	<u>WT %</u>	<u>Material</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
65997-15-1	10-20%	Portland Cement	5 mg/m ³	10 mg/m ³
65997-16-2	20-30%	Calcium Aluminate	5 mg/m ³	10 mg/m ³
108-05-4	15-25%	Vinyl Acetate Polymer	5 mg/m ³	5 mg/m ³
65996-69-2	20-30%	Slag (Recycled By-Product)	N/A	N/A

Section III – Physical /Chemical Characteristics

Boiling Point N/A	Specific Gravity (H2O = 1) 1.0	Vapor Pressure (mm Hg.) N/A
pH (wet state) 11	Vapor Density (AIR = 1) N/A	Solubility in Water Less than 0.1%
Melting Point N/A	Evaporation Rate N/A	Appearance and Odor Fine Gray Powder Low odor

Section IV – Fire and Explosion Hazard Data

Flash Point Flammable Non-Flammable	Limits Non-Flammable	LEL/UEL N/A
Extinguishing Media Will Not Burn	Special Fire Fighting Procedures None	Unusual Fire & Explosion Hazards None

Section V – Reactivity Data

Stability Stable	Conditions to Avoid N/A	Incompatibility (Materials to Avoid) Known
Hazardous Decomposition Will not occur	Hazardous Polymerization Will not occur	Conditions to Avoid N/A

Material Safety Datasheet (MSDS)- FEATHER CEMENT

Section VI – Health Hazard Data

ACUTE:

EYES:

Contact with eyes will cause irritation and possible corrosion damage and burning. Particulates can also cause mechanical irritation.

SKIN:

When mixed with water, direct contact with skin can cause irritation. If irritation occurs, rinse with water until free of material, then wash skin thoroughly with soap and water. May dry skin.

INHALATION:

Inhalation of dust from this product can irritate nose, throat, lungs, and upper respiratory tract. Persons that are subject to a large amount of dust, remove subject to fresh air. Respiratory symptoms can occur such as coughing, sneezing, and nasal irritation.

INGESTIONS:

May be corrosive to the digestive tract.

CHRONIC:

EYES:

Conjunctivitis and Keratitis, may develop after repeated contact with eyes.

SKIN:

Prolonged contact may cause dermatitis and drying of skin.

INHALATION:

Conditions such as bronchitis and emphysema have been reported after many years of exposure to Portland cement. Prolonged and repeated exposure to quartz can result in lung disease (i.e. Silicosis) and/or lung cancer.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Immediately flush eyes thoroughly with large amounts of water for 20 minutes, including upper and lower lids.

SKIN: Promptly wash with water and soap for at least 15 minutes or longer, depending on the concentration, amount and duration of exposure. If irritation persists after washing, consult a physician.

INHALATION: Remove subject to fresh air until irritation subsides, so if conditions warrant, consult a physician.

INGESTION: Seek medical attention immediately.

Material Safety Datasheet (MSDS)- FEATHER CEMENT

Signs and Symptoms of Exposure: Exposure to skin or eyes may cause rash or irritation. Inhalation may cause cough, shortness of breath, wheezing and reduced pulmonary function.

Medical Conditions Generally Aggravated by Exposure: Persons with allergies to Portland cement or individuals with respiratory disease or subject to eye irritation should not have exposure to this product.

MEDICAL CONDITIONS WHICH MAY BE AGGRIVATED: Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema, and asthma.

PRIMARY ROUTES OF ENTRY: Inhalation, eyes and/or skin contact, ingestion.

Section VII – Precautions for Safe Handling and Use

Steps to be taken in case material is released or spilled –

Spills should be swept up and contained in a waste container for disposal. Do not flush down drains. If washed down, it may plug drains. If already mixed with water, scrape up and place in container. Wear appropriate protective equipment.

Waste Disposal Method –

Dispose of in accordance with all applicable local, state/provincial and federal regulations.

Precautions to be taken in handling and storing –

Store in a cool, dry area. Take precautions to avoid bag breakage, subsequent spillage of material and dust creation.

Section VIII – Control Measures

Respiratory Protection:

Wear proper respiratory protection during mixing and during sanding if needed. Provide general ventilation and local exhaust ventilation to meet TLV requirements of individual ingredients and to control dusting conditions. Wear a NIOSH/MSHA approved respirator in poorly ventilated dusty areas and/or if TLV is exceeded. Refer to the most recent standards of ANSI (z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR PARTS) and NOISH respirator decision logic.

Ventilation:

Ventilate to keep exposures below TLV. General ventilation is expected to be satisfactory in most cases. Use local exhaust ventilation if necessary to control dust.

Protective Gloves:

Recommended

Eye Protection:

Recommended

