



SILICATE FREE HIGH PERFORMANCE ADMIXTURE

Concure Systems Admixture **PLUS S/F** is designed to stop flooring failures due to moisture migration through below-grade, on-grade and above-grade substrates.

No limits on Rh or CC testing – (Up to 100% RH and / or 50 lbs. CC if tested)

Concure Systems Admixture PLUS S/F Benefits

- LIFETIME warranty covering finish flooring / coatings, including patching compounds, adhesives and labor.
- 27+ years without a single failure.
- Does **NOT** require use of an underslab vapor barrier/retarder
- INTEGRAL in the slab and NEVER requires topical sealing, NO additional labor costs.
- FRACTION of cost to use versus topical suppressants.
- Flooring can usually be installed 30 days after pouring the concrete
- Eliminates moisture problem PERMANENTLY!
- Compatible with ALL floor coverings, coatings and approved adhesives for non-porous surfaces
- Stops ASR (Alkali-Silica-Reactivity)
- Contributes to blocking radon gas
- Works as a shrink reducing admix (SRA)
- Eliminates surface dusting
- Reduces and in some cases eliminates most slab curling due to uneven slab curing
- Minimizes spawling and surface cracks
- Eliminates efflorescence
- Inhibits rust and corrosion steel

With CONCURE Systems Admixture PLUS S/F - the concrete becomes a vapor barrier that is non-porous, impervious to moisture / moisture vapor - producing a completely sealed surface !

