

High Performance Concrete Moisture Prevention Admixture S/F (SILICATE FREE)


Concure Systems Admixture S/F is designed to stop flooring failures due to moisture migration through and out of below-grade, on-grade and above-grade slabs.

No limits: up to 100% Rh or 28 lbs. CC (if tested).

Concure Systems Admixture S/F (SILICATE FREE) Benefits:

- **LIFETIME** warranty; covering treating affected area with Concure Systems Vapor Barrier Plus, including finished flooring / coatings, patching compounds, adhesives and labor.
- Nearly 3 Decades without a single failure.
- Does NOT require use of an underslab vapor retarder/barrier
- INTEGRAL in the slab and NEVER requires topical sealing.
- FRACTION of cost to use versus topical suppressants.
- Flooring can usually be installed 30 days after pouring the concrete
- Eliminates moisture problem **PERMANENTLY!**
- Compatible with ALL floor coverings, coatings and approved adhesives for non-porous substrates
- Densifies concrete and contributes to increased concrete strength up to 125%
- Stops ASR (Alkali-Silica-Reactivity)
- Contributes to blocking radon gas
- Works as a shrink reducing admix (SRA)
- Eliminates surface dusting
- Reduces and in some cases eliminates most slab curling due to uneven slab curing
- Minimizes spawling and surface cracks
- Eliminates efflorescence

With Concure Systems Admixture S/F, the concrete becomes a vapor barrier !



Main Office: Emil Pikula - (480) 820 7171 / E M I L @ C O N C U R E S Y S T E M S . C O M Contact your local representative for additional information